

TRUCK TIRE PRODUCT PORTFOLIO



APPLICATION	LINE HAUL	REGIONAL	URBAN	ON/OFF ROAD
POSITION Steer/ All-Position	ST244 Take control of the miles ahead with this long-lasting, even-wearing steer/all-position highway tire that's SmartWay® verified.	ROUTE CONTROL® S Steer tires for fleets who value uptime, BFGoodrich brand's proven durability and traction keeps you up and running to get the job done, even in challenging conditions.	ROUTE CONTROL® S Steer tires for fleets who value uptime, BFGoodrich brand's proven durability and traction keeps you up and running to get the job done, even in challenging conditions.	CROSS CONTROL® S Get the traction, durability, and control you need for confidence in tough conditions with this long-wearing on/off road all position tire.
Drive Axle	DR454 Take control of your business with this fuel-saving, rain-fighting highway drive tire that's SmartWay® verified. DR444 Take control mile after mile with this long-lasting, rain-fighting highway and regional drive tire.	ROUTE CONTROL® D Drive tires for fleets who value uptime, BFGoodrich brand's proven durability and traction keeps you up and running to get the job done, even in challenging conditions.	ROUTE CONTROL® S Steer tires for fleets who value uptime, BFGoodrich brand's proven durability and traction keeps you up and running to get the job done, even in challenging conditions.	CROSS CONTROL® D Get the traction and durability you need to get the tough jobs done with this aggressive on/off-road drive tire.
Trailer Axle	HIGHWAY CONTROL® T Trailer tire designed to provide long, even wear and fuel efficiency to keep your fleet up and running for the long haul.	HIGHWAY CONTROL® T Trailer tire designed to provide long, even wear and fuel efficiency to keep your fleet up and running for the long haul.	Optional All-Position ROUTE CONTROL® S Steer tires for fleets who value uptime, BFGoodrich brand's proven durability and traction keeps you up and running to get the job done, even in challenging conditions.	Optional All-Position CROSS CONTROL® S Get the traction, durability, and control you need for confidence in tough conditions with this long-wearing on/off road all position tire.

* 5 Year / 2-Retread Manufacturer's Limited Casing Guarantee. See limited warranty for details.

TECHNICAL DATA

Size	Tread	Load Range	Catalog Number	Tread Depth 32nds	Max. Speed (*)		Loaded Radius		Overall Diameter		Overall Width (‡)		Approved Wheels (Measuring wheel listed first.)	Dual Spacing		Revs Per Mile	Max. Tire Load Per Axle - Single				Max. Tire Load Per Axle - Dual			
					mph	km/h	in.	mm	in.	mm	in.	mm		in.	mm		lbs	psi	kg.	kPa	lbs	psi	kg.	kPa
225/70R19.5	ROUTE CONTROL S	G	21717	15	87	140	15.1	383	32.2	817	8.8	224	6.75, 6.00	10.0	254	643	3970	110	1800	760	3750	110	1700	760
	ROUTE CONTROL D	G	83490	18	87	140	15.2	385	32.4	822	9.2	234	6.75, 6.00	10.0	254	639	3970	110	1800	760	3750	110	1700	760
245/70R19.5	ROUTE CONTROL S	H	69107	16	75	120	15.5	393	33.3	847	9.6	244	7.50, 6.75	10.9	276	623	4940	120	2240	825	4675	120	2120	825
	ROUTE CONTROL D	H	24719	19	75	120	15.5	393	33.6	845	9.9	251	7.50, 6.75	11.2	284	619	4940	120	2240	825	4675	120	2120	825
10R22.5	ST230	G	62086	17	75	120	18.6	472	39.8	1012	10.0	255	7.50, 6.75	11.4	288	521	5675	115	2575	790	5355	115	2430	790
11R22.5	DR444	G	77081	28	75	120	19.4	493	41.8	1062	11.2	284	8.25, 7.50	12.5	318	497	6175	105	2800	720	5840	105	2650	720
	DR454	G	06941	26	75	120	19.5	496	41.8	1061	11.2	284	8.25, 7.50	12.5	318	496	6175	105	2800	720	5840	105	2650	720
	HIGHWAY CONTROL T	G	97956	12	75	120	19.1	484	40.9	1038	11.2	284	8.25, 7.50	12.5	318	507	6175	105	2800	720	5840	105	2650	720
	ST244	G	40525	18	75	120	19.1	486	41.1	1043	10.5	267	8.25, 7.50	12.5	318	505	6175	105	2800	720	5840	105	2650	720
	DR444	H	98035	28	75	120	19.4	493	41.8	1062	11.2	284	8.25, 7.50	12.5	318	497	6610	120	3000	830	6005	120	2725	830
	CROSS CONTROL D	H	08038	29	68	110	19.7	501	42.1	1070	11.3	288	8.25, 7.50	12.5	318	491	6610	120	3000	830	6005	120	2725	830
	CROSS CONTROL S	H	03117	21	68	110	19.5	495	41.6	1056	11.2	284	8.25, 7.50	12.5	318	497	6940	123	3150	850	6395	123	290	850
	ROUTE CONTROL D	H	94556	26	75	120	19.5	496	41.7	1060	11.2	285	8.25	12.5	318	495	6610	120	3000	830	6005	120	2725	830
	ROUTE CONTROL S	H	03285	18	75	120	19.2	489	41.2	1045	11.2	284	8.25, 7.50	12.5	318	503	6610	120	3000	830	6005	120	2725	830
	ST230	H	68045	18	75	120	19.1	486	41.1	1043	11.1	282	8.25, 7.50	12.5	318	505	6610	120	3000	830	6005	120	2725	830
	ST244	H	92401	18	75	120	19.2	487	41.1	1044	12.2	309	8.25, 7.50	12.5	318	505	6610	120	3000	830	6005	120	2725	830
255/70R22.5	ROUTE CONTROL S	H	52587	16	75	120	17.4	441	36.5	927	10.2	258	7.50, 6.75, 8.25	11.6	295	563	5510	120	2500	830	5070	120	2300	830
275/80R22.5	DR444	G	90375	28	75	120	18.9	480	40.6	1032	10.9	277	8.25, 7.50	12.2	311	511	6175	110	2800	760	5675	110	2575	760
	DR454	G	05887	26	75	120	19.0	482	40.6	1031	10.9	277	8.25, 7.50	12.2	311	510	6175	110	2800	760	5675	110	2575	760
	HIGHWAY CONTROL T	G	70298	12	75	120	18.4	4760	39.7	1008	11.1	283	8.25, 7.50	12.2	311	522	6175	110	2800	760	5675	110	2575	760
	ROUTE CONTROL D	G	06136	26	75	120	18.6	472	39.9	1013	10.9	278	8.25	12.2	311	519	6175	110	2800	760	5675	110	2575	760
	ROUTE CONTROL S	G	39319	18	75	120	18.6	473	39.9	1014	11.0	279	8.25	12.2	311	519	6175	110	2800	760	5675	110	2575	760
	ST244	G	61456	18	75	120	18.6	472	40.0	1016	10.9	277	8.25, 7.50	12.2	311	519	6175	110	2800	760	5675	110	2575	760
315/80R22.5	ST230	L	55458	17	75	120	19.6	499	42.4	1077	12.5	317	9.00	13.8	351	489	9090	130	4125	900	8270	130	3750	900
	CROSS CONTROL S	L	97643	21	68	110	19.8	503	42.5	1081	12.6	321	9.00, 9.75	13.8	351	489	9090	130	4125	900	8270	130	3750	900
385/65R22.5	CROSS CONTROL S (wb)	J	53214	21	68	110	19.7	500	42.3	1075	14.8	377	11.75, 12.25	—	—	490	9370	123	4250	830	—	—	—	—
425/65R22.5	CROSS CONTROL S (wb)	L	19321	20	68	110	20.5	520	44.4	1128	16.5	420	13.00, 12.25	—	—	469	11400	120	5150	825	—	—	—	—
11R24.5	DR444	G	52321	28	75	120	20.5	521	43.9	1116	11.0	279	8.25, 7.50	12.5	318	472	6610	105	3000	720	6005	105	2725	720
	HIGHWAY CONTROL T	G	44529	12	75	120	20.0	507	42.9	1089	11.2	285	8.25, 7.50	12.5	318	483	6610	105	3000	720	6005	105	2725	720
	DR444	H	89861	28	75	120	20.5	521	43.9	1116	11.0	279	8.25, 7.50	12.5	318	472	7160	120	3250	830	6610	120	3000	830
	CROSS CONTROL D	H	38810	29	68	110	20.6	525	44.1	1121	11.2	285	8.25, 7.50	12.5	318	469	7160	120	3250	830	6610	120	3000	830
	CROSS CONTROL S	H	36251	21	68	110	20.4	517	43.6	1107	11.3	287	8.25, 7.50	12.5	318	479	7160	120	3250	830	6610	120	3000	830
	ROUTE CONTROL S	H	65269	18	75	120	20.2	513	43.2	1097	11.3	287	8.25	12.5	318	479	7160	120	3250	830	6610	120	3000	830
	ROUTE CONTROL D	H	47051	26	75	120	20.5	520	43.9	1110	10.5	269	8.25	12.5	318	473	7160	120	3250	830	6610	120	3000	830
	ST244	H	58109	18	75	120	20.2	513	43.3	1100	11.0	279	8.25, 7.50	12.5	318	478	7160	120	3250	830	6610	120	3000	830
275/80R24.5	DR444	G	55617	28	75	120	19.5	495	41.9	1064	10.6	269	8.25, 7.50	12.2	311	500	6175	110	2800	760	5675	110	2575	760
	ST230	G	71892	18	75	120	19.2	488	41.3	1049	10.6	269	8.25, 7.50	12.2	311	503	6175	110	2800	760	5675	110	2575	760
	ST244	G	77897	18	75	120	19.2	488	41.3	1049	10.6	269	8.25, 7.50	12.2	311	502	6175	110	2800	760	5675	110	2575	760
285/75R24.5	HIGHWAY CONTROL T	G	26773	12	75	120	19.1	486	40.8	1037	10.7	273	8.25	12.5	318	507	6175	110	2800	760	5675	110	2575	760
	ROUTE CONTROL S	G	05454	18	75	120	19.3	490	41.1	1045	10.7	272	8.25, 7.50	12.2	311	503	6175	110	2800	760	5675	110	2575	760

Note: Wheel listed first is the measuring wheel.
(*) Exceeding the lawful speed limit is neither recommended nor endorsed.
(‡) Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.
MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect the current Load and Inflation information. Please visit www.michelintruck.com for the latest product information. Note: The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits without permission from the component manufacturer.

To Find Your Nearest BFGoodrich® Commercial Truck Tire Dealer
Call: United States, 1-877-788-8899; Canada, 1-888-871-6666
or visit www.bfgoodrichtrucktires.com
© 2023 MNA, Inc. All rights reserved. PDF only (10/23)
© 2023 MNA(C)I All rights reserved.